







RFID based Access Control System

|  PRODUCTS | | | |
|--|-------------------------------|--|------------------------|
| TTA0C3-RFID  RFID Access Control System | | Tutis RFID system is an innovative Proximity card reader used in Access Control applications and can be installed standalone or with any third party panel that supports 64-bit Wiegand. User will benefit from their unparalleled performance using the state of the art proximity reader and embedded Linux platform | |
|  FEATURES | | | |
| <ul style="list-style-type: none"> • Stores 10000 cards and 50000 transactions • Read Cards and or/PINs • Built in Serial and Ethernet ports • Multi Language Support • Built in Bell scheduling • Audio-Visual indications for acceptance and rejection of valid/invalid cards • 4 x 4 metal keypad with 4 function keys | | | |
|  Technical Specifications | | | |
| Capacity | | Verification/Identification | |
| Templates: | 10000 | Matching: | 1:N up to 10000 users |
| Transactions: | 50000 | Verification: | ≤1 second |
| | | Identification: | ≤2 seconds |
| | | Enrollment: | ≤5 seconds |
| | | FRR | ≤1% |
| | | FAR | ≤0.001% |
| Display | | Environment | |
| LCD: | 4 x 16 Characters LCD Display | Oper. Temp: | 32° - 105 °F (0°-42°C) |
| Communication | | Power | |
| Port: | RS 232/RS 485 | Oper. Voltage: | 12 V DC |
| Port: | Ethernet 10/100 | | |
| Dimensions | | | |
| Length: | 8.46 inches (215mm) | | |
| Width: | 6.88 inches (175mm) | | |
| Depth: | 2.4 inches (50mm) | | |

TUTIS TECHNOLOGIES LTD.

Regd. Office : C-409, Solaris 1, Opp. L&T Gate No. 6, Saki Vihar Road, Andheri (E), Mumbai - 400072. INDIA.
 Tel.: (91-22) 2857 8240/42 Fax : (91-22) 2857 8239 Email : info@tutistech.com Website : www.tutistech.com